Compact Speakers

WS-A10E (Black)
WS-A10E-W (White)

WS-A10E-W
(White)

WS-A10E
(Black)

Input terminals

(Two types of speaker terminal : phone jack and push-type wire terminal)

- Full-range, Bass Reflex speaker in a compact size; 88 dB SPL, 6 Ω
- Wide frequency response of 50 Hz to 20 kHz
- High power handling capacity of 160 W (continuous program input)/80 W (RMS)
- Wide dispersion even at high frequency for stable tonal balance: 40˚(H) x 40˚(V); trapezoidal enclosure allows the driver to be vertical or tilted 25˚ in either direction when resting on a horizontal surface.
- Thermal protection to prevent damage caused by accidental excessive input
- Low magnetic leakage.
- Push-type wire terminals

Directivity



Frequency Response



Dimensions



Unit: mm

SPECIFICATIONS

Speaker Type		Full Range
Input Impedance		6 Ω
Power Handling Capacity		160 W (continuous program input) 80 W (RMS)
Sensitivity		88 dB SPL (1 W, 1 m)
Frequency Response		50 Hz~20 kHz
Drivers		12 cm (5") cone type
Dispersion		40˚ (H) x 40˚ (V)
Dimensions		250 (W) x 155 (H) x 156 (D) mm
Weight (approx.)		2.6 kg
Finish	**Enclosure**	Molded resin,black or off-white
	Front Panel	Punched grille,black or off-white